ARRICAM Lite - Wireless Remote System (WRS)

CONFIGURATION OVERVIEW – **1.5.1 / 2010.07**

© 2010 Arnold & Richter Cine Technik GmbH & Co. Betriebs KG. All rights reserved. This material is provided "as is" for information purposes only without any warranty.
ARRI assumes no responsibility with regard to the performance or use of the products or typographical errors or inaccuracies of given information. Product specifications are subject to change without notice. For a full listing of all available components consult the price list.

WRS Components

Wireless Main Unit WMU-3, K2.52240.0
Antenna, 05.20112.0

Wireless Focus Unit WFU-3, K2.52268.0
Marking Disks, Bevelled, K4.47621.0
Flat, K2.47292.0

Wireless Zoom Unit WZU-3 K2.52267.0

Wireless Remote Control, WRC-2 K0.60042.0

Lens Data Display for Focus Puller LDD-FP K2.54163.0

Zoom Main Unit ZMU-3A K2.65003.A

Wired Handgrip Attachment WHA-3 K2.54079.0

Wireless Battery Unit WBU-3, K2.52238.0
Wireless Battery Unit WBU-4, K2.65001.0

Wireless Compact Unit WCU-3, K2.65155.0

Wireless Zoom Extension, WZE-3 K2.65150.0

Battery (Sony) NP-FM 500 H, K2.47851.0
Charger (Sony) BC-M50, K2.47852.0

Wireless Accu Charger WAC-3, K2.52266.0

Wireless Expansion Bracket, WEB-3 K2.52241.0

Wireless Zoom Bracket, WZB-3 K2.65017.0

ZMU-3 Bracket for WCU-3, K2.65132.0
Connection cable KC-192 S needed K2.65132.0

WHA-2 Rod Bracket K2.52150.0

wireless:

wired



to Antenna
WC-A3 =15m
WC-A2 =3m

to LCS Plug:
LC-M1 = 1m
LC-Z1 = 3,5m

LC-E1 = 75m

Data Receivers

Lite Lens Data Box-2 K2.54195.0

up to 3 Controlled Lens Motor
CLM-2, K2.52036.0
CLM-3, K0.60057.0
or CLM-1 for
Focus, Iris, Zoom

Remote Options

Camera Control Funkctions:

- **Focus**
- **Zoom**
- **Iris**

- **Speed, 1 - 48 fps**
- **Shutter, 11,2∞ - 180∞**
- **Ramps**
- **Run/Stop**

Calculations:

- **Depth of Field**
- **Hyperfocal Distance**

Wireless Control: Sample Configurations

WBU-3, WMU-3
WZU-3, WFU-3

WRC-2, WMU-3
WEB-3
WFU-3, WBU-3

ZMU-3A, WCU-3

WBU-3, WMU-3
WFU-3, ZMU-3A
WZB-3

WCU-3

Wired Control: Configuration Samples

to CAC Plug:
KC 65 = 3m/9,8ft
KC 69 = 15m/50ft
Drum = 50m/164ft

RCS, Remote Control Station K2.54143.0

WZU-3 + or **WFU-3** or **WRC-1** or **WRC-2**

MCB **TSB**

CAC Distribution-3

SCB

WHA-3

LC-E1 = 75m

LC-M1 = 1m
LC-Z1 = 3,5m

WEU-1

WMA-1

Cable:
WC-E1/2

WHA-1

WFU-3

Data Display & Input Devices

LDD-FP
Lens Data Display
for Focus Puller

LDD FP RDO Cable K2.54172.0

Lite Mask Framglow

LDD
Lens Data Display
Classic

LDD Cable KC60 SP-S K4.55855.0

Lite LDB

KC-67-S = 3m K2.54132.0
KC-68-S = 15m K2.54133.0

CAC Plug

Pick Up Box K4.43313.0

KC-66-S = 10m K2.54129.0

SCB

Cine Tape Measure

K-CAC-CTM-Sp-S K2.52265.0

CAC Plug